

# Installation

UikFix Laptop Keyboard



Hinge Series: 66

Difficulty: **Easy**

## Step One


Verify all materials are included.

Be sure your purchase contains the materials you've requested. This includes the key cap, the hinge mechanism and a rubber cup (optional) which will be under the key when installation is finished.



## Step Two

Orient hinge correctly and begin installation.



To install the hinge piece, begin by hooking one end over the protruding metal tabs located on the keyboard. A small flat screwdriver or blunt tweezers will assist you in this step. Keep the flattest side of the hinge facing up so it is able to properly receive the key cap.

## Step Three

Complete hinge mechanism install.

Press the other ends of the hinge mechanism onto the alternate brackets and it will lock into place. Be careful with this step, as forcing the hinge or placing too much stress on the hinge may cause it to break! Once both hinge pieces are installed, the metal stabilizer bar(s) (if included) can be placed into their respective brackets on the keyboard. These may need to be removed from the underside of the key cap before installing.



## Step Four

Install rubber cup (optional) and press key cap into place.



With the hinge now properly installed, you can place the optional rubber cup if needed. This can be set into the center of the hinge assembly. If using adhesive, apply a **small** amount of glue around the **OUTER** rim of the cup and seat it in the center of the hinge assembly. **Allow ample drying time before installing the key cap!** Then, simply place the correctly oriented key cap over the hinge mechanism and press down. If the key cap clicks into place, you're all done!